

DAYTON

LONG HAUL SERVICE

The Dayton lineup of SmartWay® verified tires are built for those who spend their days on the road. These long-haul application tires are designed to combat irregular wear while the tread compound reduces rolling resistance, which can help you save fuel and money.

 EPA SMARTWAY® VERIFIED



 **D510S STEER**

ALL-POSITION ON-HIGHWAY TIRE RECOMMENDED FOR THE STEER POSITION IN LONG HAUL SERVICE FOR TRUCKLOAD AND LTL APPLICATIONS

- Defense groove and stabilizer rib design help prevent initiation of irregular wear
- Groove bottom platforms in central ribs helps protect casing against stone retention
- Tread compound designed to reduce rolling resistance and contribute to fuel efficiency

TIRE SIZE	LOAD RANGE	TREAD DEPTH (32"/mm)	MAX TIRE LOAD (SINGLE) (Lbs@PSI/Kg@kPa)	(DUAL) (Lbs@PSI/Kg@kPa)	MAX SPEED (mph/kph)
11R22.5 METRIC	G	19 15	6175@105 2800@720	5840@105 2650@720	75 120
11R22.5 METRIC	H	19 15	6610@120 3000@830	6005@120 2725@830	75 120
295/75R22.5 METRIC	G	20 16	6175@110 2800@760	5675@110 2575@760	75 120
11R24.5 METRIC	G	19 15	6610@105 3000@720	6005@105 2725@720	75 120
285/75R24.5 METRIC	G	19 15	6175@110 2800@760	5675@110 2575@760	75 120



 **D610D DRIVE**

ON-HIGHWAY TIRE RECOMMENDED FOR THE DRIVE POSITION IN LONG HAUL SERVICE FOR TRUCKLOAD AND LTL APPLICATIONS

- Deep, aggressive pattern for reliable traction and long tread life
- Closed shoulder design offers tread stability and helps prevent initiation of irregular wear
- Tread compound designed to reduce rolling resistance and contribute to fuel efficiency

TIRE SIZE	LOAD RANGE	TREAD DEPTH (32"/mm)	MAX TIRE LOAD (SINGLE) (Lbs@PSI/Kg@kPa)	(DUAL) (Lbs@PSI/Kg@kPa)	MAX SPEED (mph/kph)
11R22.5 METRIC	G	27 21	6175@105 2800@720	5840@105 2650@720	75 120
11R22.5 METRIC	H	27 21	6940@123 3150@850	6395@123 2900@850	75 120
295/75R22.5 METRIC	G	27 21	6175@110 2800@760	5675@110 2575@760	75 120
11R24.5 METRIC	G	27 21	6610@105 3000@720	6005@105 2725@720	75 120
11R24.5 METRIC	H	27 21	7160@120 3250@830	6610@120 3000@830	75 120
285/75R24.5 METRIC	G	27 21	6175@110 2800@760	5675@110 2575@760	75 120



 **D410T TRAILER**

ON-HIGHWAY TIRE RECOMMENDED FOR THE TRAILER POSITION IN LONG HAUL AND REGIONAL SERVICE FOR TRUCKLOAD, LTL, AND DISTRIBUTION AND P&D APPLICATIONS

- Five streamlined ribs distribute contact pressure for even wear
- Four circumferential grooves provide efficient water evacuation
- Tread compound designed to reduce rolling resistance and contribute to fuel efficiency

TIRE SIZE	LOAD RANGE	TREAD DEPTH (32"/mm)	MAX TIRE LOAD (SINGLE) (Lbs@PSI/Kg@kPa)	(DUAL) (Lbs@PSI/Kg@kPa)	MAX SPEED (mph/kph)
11R22.5 METRIC	G	11 9	6175@105 2800@720	5840@105 2650@720	75 120
295/75R22.5 METRIC	G	11 9	6175@110 2800@760	5675@110 2575@760	75 120
11R24.5 METRIC	G	11 9	6610@105 3000@720	6005@105 2725@720	75 120
285/75R24.5 METRIC	G	11 9	6175@110 2800@760	5675@110 2575@760	75 120
255/70R22.5 METRIC	H	13 10	5510@120 2500@830	5070@120 2300@830	75 120